

Amendments to the Specification

Please replace the paragraph beginning at page 11, line 20, with the following amended paragraph:

The isolated bus cycle interface 152 includes circuitry to interface to the isolated bus cycle signals to recognize and service isolated bus cycles, such as the isolated read and write bus cycles. The processor nub loader 52, as shown in Figure 1A, includes a processor nub loader code and its digest (e.g., hash) value. The processor nub loader 52 is invoked by execution of an appropriate isolated instruction (e.g., Iso_Init) and is transferred to the isolated area 70. From the isolated ~~area 80~~ area 70, the processor nub loader 52 copies the processor nub 18 from the system flash memory (e.g., the processor nub code 18 in non-volatile memory 160) into the isolated area 70, verifies and logs its integrity, and manages a symmetric key used to protect the processor nub's secrets. In one embodiment, the processor nub loader 52 is implemented in read only memory (ROM). For security purposes, the processor nub loader 52 is unchanging, tamper-resistant and non-substitutable. The digest memory 154, typically implemented in RAM, stores the digest (e.g., hash) values of the loaded processor nub 18, the operating system nub 16, and any other critical modules (e.g., ring-0 modules) loaded into the isolated execution space. The cryptographic key storage 155 holds a symmetric encryption/decryption key that is unique for the platform of the system 100. In one embodiment, the cryptographic key storage 155 includes internal fuses that are programmed at manufacturing. Alternatively, the cryptographic key storage 155 may also be created with a random number generator and a strap of a pin. The isolated execution logical processor manager 156 manages the operation of logical processors operating in isolated execution mode. In one embodiment, the isolated execution logical processor manager 156 includes a logical processor count register that tracks the number of logical processors participating in the isolated execution mode. The token bus interface 159 interfaces to the token bus 180. A combination

of the processor nub loader digest, the processor nub digest, the operating system nub digest, and optionally additional digests, represents the overall isolated execution digest, referred to as isolated digest. The isolated digest is a fingerprint identifying the ring-0 code controlling the isolated execution configuration and operation. The isolated digest is used to attest or prove the state of the current isolated execution.